

HAVIS DOCKING STATIONS FOR GETAC ZX80 TABLETS

DS-GTC-1500 SERIES



POWERING PRODUCTIVITY IN WAREHOUSES

- Optional port replication with Advanced or Standard content
- LED power indicator
- Optional triple pass-thru antenna connection
- Dual stylus holders on left & right sides of dock
- One-handed docking & undocking
- Spring-loaded connector head
- Compact & lightweight
- Includes power supply cable (DS-DA-339)
- Supports Getac ZX80 extended batteries and stylus handstrap
- Integrated cable management system
- Integrated VESA 75 mounting pattern

HAVIS DOCKING STATIONS FOR GETAC ZX80 TABLETS

DS-GTC-1500 SERIES

GETAC ZX80 TABLET SOLUTION

- Compact design with one-handed docking & undocking
- Advanced port replication & cradle option available
- Triple pass-thru antenna connection (optional)
- Access to all buttons & ports when docked



PART NUMBER	USB 2.0	ETHERNET	POWERED SERIAL	POWER INPUT	PASS-THRU ANT	ANT TYPE
DS-GTC-1501	1 REAR			9-36VDC		
DS-GTC-1501-3	1 REAR			9-36VDC	TRIPLE	SMA
DS-GTC-1502	2 REAR	1 REAR	1 REAR	9-36VDC		
DS-GTC-1502-3	2 REAR	1 REAR	1 REAR	9-36VDC	TRIPLE	SMA
DS-GTC-1503						
DS-GTC-1503-3					TRIPLE	SMA
DS-GTC-1506				LPS-175		
DS-GTC-1506-3				LPS-175	TRIPLE	SMA

SPECIFICATIONS:

Height: 8.08" in (205mm)
Width: 9.12" in (233mm)
Depth: 2.94" (75mm)
Weight: 2.23 lb (1.01 kg)
Mounting: VESA 75

CERTIFICATIONS & TESTING:

E-Mark, CE Certified; RoHS Compliant
Vibration Testing: MIL-STD 810H 514.8
Crash Testing: SAE J1455 30mph
Cycle Testing: Latch handle and docking connectors 30K cycles
Environmental Testing: Hot/Cold operational -29° C to 63° C (-20.2° F to 145.4° F); Hot/Cold storage -40° C to 85° C (-40° F to 185° F)

