

RUGGED DOCKING STATIONS FOR ZEBRA ET80 & ET85 12" TABLETS

DS-ZEB-400 SERIES



OPTIMIZED EFFICIENCY IN WAREHOUSE ENVIRONMENTS

- Standard & advanced I/O options
- External isolated and non-isolated power options available
- LED power indicator
- One-handed docking & undocking
- Spring-loaded, floating connector head
- Provides access to critical buttons, ports & barcode scanner when docked
- Compact & lightweight design
- Compatible with Zebra stylus tether, Stylus MPP 2.0, handle with stylus holder & shoulder strap
- Intelligent cable management system
- Integrated VESA 75 mounting pattern

RUGGED DOCKING STATION FOR ZEBRA ET80 & ET85 12" TABLETS

DS-ZEB-400 SERIES

ET8X TABLET SOLUTION

- Supports Windows Devices
- Low profile, lightweight and compact design
- Standard & advanced port replication (optional)
- External isolated and non-isolated power options available
- LED power indicator



PART NUMBER	ETHERNET	USB-C	USB 3.0	HDMI	POWERED SERIAL	POWER INPUT	PASS-THRU ANT	ANT TYPE
DS-ZEB-401	1	1 REAR	2 REAR 1 SIDE		1 @ 5V	19.5VDC*		
DS-ZEB-401-3	1	1 REAR	2 REAR 1 SIDE		1 @ 5V	19.5VDC*	TRIPLE	SMA
DS-ZEB-402	1	1 REAR	2 REAR 1 SIDE	1	1 @ 5V	19.5VDC*		
DS-ZEB-402-3	1	1 REAR	2 REAR 1 SIDE	1	1 @ 5V	19.5VDC*	TRIPLE	SMA
DS-ZEB-403								

*Requires an external Havis-approved DC power supply

SPECIFICATIONS:

Height: 11.25-in (28.57 cm)
 Width: 13-in (33 cm)
 Depth: 3.42-in (8.68 cm)
 Weight: 2.58 lbs. (1.1kg)
 Mounting: Integrated VESA 75 - mounting pattern

CERTIFICATIONS & TESTING:

CE certified; UKCA and RoHS compliant
 Vibration testing: MIL-STD 810H 514.8
 Crash testing: SAE J1455 30 mph
 Cycle test: Latch handle and docking connectors 30K cycles
 Environmental testing: Hot/cold operation & storage

