

DOCKING STATIONS FOR GETAC V120 LAPTOPS

Getac



BUILT FOR PERFORMANCE

This reengineered series of docking stations for Getac® V120 laptops now offers a relocated RF antenna and improved cable routing for cleaner installs. Engineered for heavy vibration use, the spring-loaded connector ensures your device remains connected in mobile applications.

- Redesigned with relocated RF antenna and improved cable routing.
- Choose between advanced or standard port replication.
- Quad pass-through antenna connection (select models).
- Ensure maximum reliability in heavy vibration with the screen support add-on.*
- Attach the power supply directly to the dock with the accessory bracket for cleaner installs.**
- Spring loaded connector for uninterrupted connection in high vibration environments.
- Integrated lock for theft deterrence.
- Power supply included (select models).

*DS-DA-424 **LPS-211





GETAC V120 LAPTOP SOLUTION

A compact, rugged docking solution for the Getac V120 laptop. Built for heavy vibration use, it delivers fast, dependable docking that keeps your device secure through daily mobile operation.

- Intelligent cable management system
- Designed to fit all Havis and VESA 75 hole pattern mounting equipment
- Polycarbonate construction ensures strength, ruggedness and extreme temperature resistance



PART DETAILS

PART NUMBER	ETHERNET (RJ45)	USB-A	USB-C	HDMI	POWERED SERIAL (DB9)	PASS-THRU ANT (QUAD)	EXT POWER
DS-GTC-1611	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)		1		
DS-GTC-1611-4	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)		1	1	
DS-GTC-1612-BW	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)		1		LPS-140-BW
DS-GTC-1612-4-BW	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)		1	1	LPS-140-BW
DS-GTC-1613							
DS-GTC-1613-4						1	
DS-GTC-1614	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)	1	1		
DS-GTC-1614-4	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)	1	1	1	
DS-GTC-1615-BW	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)	1	1		LPS-140-BW
DS-GTC-1615-4-BW	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)	1	1	1	LPS-140-BW

SPECIFICATIONS

HEIGHT: 11.8" / 29.97 CM

WIDTH: 11.1" / 28.19 CM

DEPTH: 3.1" / 7.87 CM

WEIGHT: 4.7 LBS / 2.13 KG

MOUNTING: VESA 75

CERTIFICATIONS & TESTING

VIBRATION TESTING

MIL-STD 810H 514.8

CRASH TESTING

SAE J1455 30MPH

BUMP TESTING

IEC-68-2006-27

CYCLE TESTING

DOCK/UNDOCK 30K CYCLES

ENVIRONMENTAL TESTING

HOT/COLD OPERATIONAL -29° C TO 63° C (-20° F TO 145° F)
HOT/COLD STORAGE -40° C TO 85° C (-40° F TO 185° F)

THERMAL SHOCK

MIL-STD 810H, METHOD 503.7

EMC TESTING

EN 55032, EN 50498

ESD

IEC 10605

