

RUGGED KEYBOARD WITHOUT EMERGENCY KEY



SPECIFICATIONS

DIMENSIONS	11.98"L X 7.73"W X 1.25"D
MOUNTING	VESA 75 & AMPS
COMMUNICATION INTERFACE	USB-A (1)
WORKING VOLTAGE	5V + 5%/-10 THROUGH USB PORT
CURRENT CONSUMPTION	MAX 200mA
OPERATING ENVIRONMENT	-20°C TO +70°C
OPERATING HUMIDITY	99%
STORAGE ENVIRONMENT	-20°C TO +70°C
PRODUCT WEIGHT	1.7 LBS

TESTING

DROP: MIL-STD-810H 516.8
VIBRATION: MIL-STD-810H 514.8
CRASH: SAE J1455 30MPH
CYCLE: DOCK AND UNDOCK FOR 20K CYCLES
ENVIRONMENTAL:
 HOT/COLD OPERATING -20°C TO 50°C (-4°F TO 122°F)
 HOT/COLD STORAGE -40°C TO 85°C (-40°F TO 185°F)

- Warehouse, transportation /logistics, work truck
- Easy to locate emergency key sends distress signal
- Keyboard features **83 keys with integrated touchpad**
- Enhanced F1 through F12 function keys to increase productivity
- Red monochrome illumination backlight for reduced eye strain
- Integrated Num Lock pad with LED
- Silicone rubber keyboard for easy cleaning
- Easily installed plug and play drivers
- Standard USB-A connection allows for connection to docking station or direct to computing device
- New Function key options include screen rotation, screen blanking, and cleaning
- IP65 rated design
- Coiled cable makes it easy to replace in the field
- Integrated VESA mounting pattern

PART DETAILS

HAVIS PART ID	COLOR	TOUCHPAD LOCATION	BACKLIGHT COLOR	# OF KEYS	NUMBER PAD	USB	BLUETOOTH	IP RATING	KEY MATERIAL
KB-1002	● BLACK	CENTER	● RED	83	✗	✓	✗	IP65	PLASTIC