

DOCKING STATIONS FOR GETAC G140 TABLETS

Getac



BUILT FOR PERFORMANCE

Secure docking for the Getac® G140 tablet, designed for demanding environments. A spring-loaded connector supports reliable connectivity, while rugged construction and integrated cable management protect equipment in daily use.

- Optional port replication with Advanced or Standard content
- Optional Quad pass-through antenna connection
- Optional LPS-208 and LPS-211 accessory bracket for mounting the power supply directly to the docking station
- Spring-loaded, floating connector head
- Getac Power Supply Included - LPS-140-BW (Select Models)
- Compatible with G140's stylus/digitizer, hard handle, high capacity batteries, and smart card reader
- Lock and key supplied for peace of mind theft deterrence
- Intelligent cable management system



GETAC G140 TABLET SOLUTION

A compact, rugged docking station for the Getac G140 tablet. Designed to withstand vibration and daily use while supporting fast, dependable docking.

- Integrated VESA 75 mounting pattern
- Polycarbonate construction ensures strength, ruggedness and extreme temperature resistance
- Rounded edges and corners for comfort and safety



PART DETAILS

PART NUMBER	ETHERNET (RJ45)	USB-A	USB-C	HDMI	POWERED SERIAL (DB9)	PASS-THRU ANT (QUAD)	EXT POWER
DS-GTC-1801	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)		1		
DS-GTC-1801-4	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)		1	1	
DS-GTC-1802-BW	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)		1		LPS-140-BW
DS-GTC-1802-4-BW	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)		1	1	LPS-140-BW
DS-GTC-1803							
DS-GTC-1803-4						1	
DS-GTC-1804	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)	1	1		
DS-GTC-1804-4	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)	1	1	1	
DS-GTC-1805-BW	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)	1	1		LPS-140-BW
DS-GTC-1805-4-BW	1	1 FRONT (2.0) 2 REAR (3.2)	1 FRONT (2.0) 1 REAR (3.2)	1	1	1	LPS-140-BW

SPECIFICATIONS

HEIGHT: 11.6" / 29.46 CM

WIDTH: 11.9" / 30.23 CM

DEPTH: 2.9" / 7.37 CM

WEIGHT: 3 LBS / 1.36 KG

MOUNTING: VESA 75

CERTIFICATIONS & TESTING

VIBRATION TESTING

MIL-STD 810H 514.8

CRASH TESTING

SAE J1455 30MPH

BUMP TESTING

IEC-68-2006-27

CYCLE TESTING

DOCK/UNDOCK 30K CYCLES

ENVIRONMENTAL TESTING

HOT/COLD OPERATIONAL -29° C TO 63° C (-20.2° F TO 145.4° F)
HOT/COLD STORAGE -51.1° C TO 71° C (-60° F TO 159.8° F)

THERMAL SHOCK

MIL-STD 810H, METHOD 503.7

EMC TESTING

EN 55032, EN 50498

ESD

IEC 10605