



RUGGED DOCKING STATIONS FOR ZEBRA ET80 & ET85 12" TABLETS

DS-ZEB-400 SERIES



ENHANCED OPERATIONAL CAPABILITY FOR RUGGED APPLICATIONS

- Standard & advanced I/O options
- External isolated and non-isolated power options available
- LED power indicator
- One-handed docking & undocking
- Spring-loaded, floating connector head
- Provides access to critical buttons, ports & barcode scanner when docked
- Compact & lightweight design
- Compatible with Zebra stylus tether, Stylus MPP 2.0, handle with stylus holder & shoulder strap
- Intelligent cable management system
- Integrated VESA 75 mounting pattern





RUGGED DOCKING STATION FOR ZEBRA ET80 & ET85 12" TABLETS

DS-ZEB-400 SERIES

ET8X TABLET SOLUTION

- Supports Windows Devices
- Low profile, lightweight and compact design
- Standard & advanced port replication (optional)
- External isolated and non-isolated power options available
- LED power indicator



| PART NUMBER | ETHERNET | USB-C | USB 3.0 | HDMI | POWERED SERIAL | POWER INPUT | PASS-THRU ANT | ANT TYPE |
|--------------|----------|--------|------------------|------|-------------------|-------------|---------------|----------|
| DS-ZEB-401 | 1 | 1 REAR | 2 REAR 1 SIDE | | 1 @ 5V | 19.5VDC* | | |
| DS-ZEB-401-3 | 1 | 1 REAR | 2 REAR 1 SIDE | | 1 @ 5V | 19.5VDC* | TRIPLE | SMA |
| DS-ZEB-402 | 1 | 1 REAR | 2 REAR 1 SIDE | 1 | 1 @ 5V | 19.5VDC* | | |
| DS-ZEB-402-3 | 1 | 1 REAR | 2 REAR 1 SIDE | 1 | 1 @ 5V | 19.5VDC* | TRIPLE | SMA |
| DS-ZEB-403 | | | | | | | | |

^{*}Requires an external Havis-approved DC power supply

SPECIFICATIONS:

Height: 11.25-in (28.57 cm) Width: 13-in (33 cm) Depth: 3.42-in (8.68 cm) Weight: 2.58 lbs. (1.1kg) Mounting: Integrated VESA 75 -

mounting pattern

CERTIFICATIONS & TESTING:

CE certified; UKCA and RoHS compliant Vibration testing: MIL-STD 810H 514.8 Crash testing: SAE J1455 30 mph

Cycle test: Latch handle and docking connectors 30K cycles Environmental testing: Hot/cold operation & storage

