



TOOL LIST

1. #2 PHILLIPS SCREW DRIVER OR DRILL DRIVER.
2. #3 PHILLIPS SCREW DRIVER OR DRILL DRIVER
3. Ø 5/32 DRILL BIT (.156") DIAMETER DRILL BIT WITH DRILL DRIVER

ASSEMBLY STEPS:

1. USING THE **SWIVEL BASE STAND** AS A TEMPLATE, ROTATE LEFT/RIGHT TO STOP POINTS TO DETERMINE DIRECTION OF SWIVEL BEFORE MOUNTING.
2. MARK MOUNTING LOCATION ON **COUNTER**
3. DRILL 5/32 HOLES IN MARKED LOCATION ON **COUNTER**
4. (OPTIONAL) DRILL A 1 3/8" (1.375") THROUGH HOLE INTO YOUR **COUNTER** AS SHOWN.
5. ATTACH THE **PAYMENT STAND** TO THE **COUNTER** BY USING THE **4X #12X 2.00" LONG PHILLIPS FLAT HEAD SCREWS** AS SHOWN.
6. ASSEMBLE THE **CREDIT CARD MACHINE** TO THE **STAND** USING THE **4X M3 X 8MM LONG PHILLIPS SCREWS** AS SHOWN.
7. INSTALL THE **UPPER ANTI-SKIMMING BRACKET** USING THE **2X #8-32 X .25" LONG PHILLIPS SCREWS** AS SHOWN.
8. ROUTE THE **MACHINE CABLES** THROUGH THE **CABLE CLIP** AND SECURE WITH THE **#8-32 X .25" LONG PHILLIPS SCREW** AS SHOWN.

DWG. NO. PTM-EQU-01		REV. A	TITLE PAYMENT TERMINAL STAND 75MM VESA FOR EQUINOX 8700x	<div>HAVIS</div> <div>SHEET 1 OF 1</div>	REVISIONS				
DRAWN J. TERVEER		DATE 7/11/2024			REV	DESCRIPTION	DATE	BY	CHK'D
					A		07/11/24	JVT	JVT
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HAVIS, INC. AND REPRODUCTION IN PART OR IN WHOLE WITHOUT THE WRITTEN PERMISSION OF HAVIS, INC. IS PROHIBITED.					CUSTOMER INSTRUCTIONS				