

DOCKING STATIONS FOR GETAC G140 TABLETS

Getac



BUILT FOR PERFORMANCE

Secure docking for the Getac® G140 tablet, designed for demanding environments. A spring-loaded connector supports reliable connectivity, while rugged construction and integrated cable management protect equipment in daily use.

- Optional port replication with Advanced or Standard content
- Optional Quad pass-through antenna connection
- Optional LPS-208 and LPS-211 accessory bracket for mounting the power supply directly to the docking station
- Spring-loaded, floating connector head
- Getac Power Supply Included - LPS-140-BW (Select Models)
- Compatible with G140's stylus/digitizer, hard handle, high capacity batteries, and smart card reader
- Lock and key supplied for peace of mind theft deterrence
- Intelligent cable management system





GETAC G140 TABLET SOLUTION

A compact, rugged docking station for the Getac G140 tablet. Designed to withstand vibration and daily use while supporting fast, dependable docking.

- Integrated VESA 75 mounting pattern
- Polycarbonate construction ensures strength, ruggedness and extreme temperature resistance
- Rounded edges and corners for comfort and safety



PART DETAILS

| PART NUMBER | ETHERNET (RJ45) | USB-A | USB-C | HDMI | POWERED SERIAL (DB9) | PASS-THRU ANT (QUAD) | EXT POWER |
|------------------|-----------------|-------------------------------|-------------------------------|------|----------------------|----------------------|------------|
| DS-GTC-1801 | 1 | 1 FRONT (2.0) 2 REAR (3.2) | 1 FRONT (2.0) 1 REAR (3.2) | | 1 | | |
| DS-GTC-1801-4 | 1 | 1 FRONT (2.0) 2 REAR (3.2) | 1 FRONT (2.0) 1 REAR (3.2) | | 1 | 1 | |
| DS-GTC-1802-BW | 1 | 1 FRONT (2.0) 2 REAR (3.2) | 1 FRONT (2.0) 1 REAR (3.2) | | 1 | | LPS-140-BW |
| DS-GTC-1802-4-BW | 1 | 1 FRONT (2.0) 2 REAR (3.2) | 1 FRONT (2.0) 1 REAR (3.2) | | 1 | 1 | LPS-140-BW |
| DS-GTC-1803 | | | | | | | |
| DS-GTC-1803-4 | | | | | | 1 | |
| DS-GTC-1804 | 1 | 1 FRONT (2.0) 2 REAR (3.2) | 1 FRONT (2.0) 1 REAR (3.2) | 1 | 1 | | |
| DS-GTC-1804-4 | 1 | 1 FRONT (2.0) 2 REAR (3.2) | 1 FRONT (2.0) 1 REAR (3.2) | 1 | 1 | 1 | |
| DS-GTC-1805-BW | 1 | 1 FRONT (2.0) 2 REAR (3.2) | 1 FRONT (2.0) 1 REAR (3.2) | 1 | 1 | | LPS-140-BW |
| DS-GTC-1805-4-BW | 1 | 1 FRONT (2.0) 2 REAR (3.2) | 1 FRONT (2.0) 1 REAR (3.2) | 1 | 1 | 1 | LPS-140-BW |

SPECIFICATIONS

- HEIGHT: 11.6" / 29.46 CM
- WIDTH: 11.9" / 30.23 CM
- DEPTH: 2.9" / 7.37 CM
- WEIGHT: 3 LBS / 1.36 KG
- MOUNTING: VESA 75

CERTIFICATIONS & TESTING

| | |
|-----------------------|--|
| VIBRATION TESTING | MIL-STD 810H 514.8 |
| CRASH TESTING | SAE J1455 30MPH |
| BUMP TESTING | IEC-68-2006-27 |
| CYCLE TESTING | DOCK/UNDOCK 30K CYCLES |
| ENVIRONMENTAL TESTING | HOT/COLD OPERATIONAL -29° C TO 63° C (-20.2° F TO 145.4° F) HOT/COLD STORAGE -51.1° C TO 71° C (-60° F TO 159.8° F) |
| THERMAL SHOCK | MIL-STD 810H, METHOD 503.7 |
| EMC TESTING | EN 55032, EN 50498 |
| ESD | IEC 10605 |

