

RUGGED RUBBER BACKLIT KEYBOARD WITH INTEGRATED POINTING DEVICE



SPECIFICATIONS

DIMENSIONS	12"L x 6"W x 1.5"D (340.80 x 152.40 x 38.10 mm)
MOUNTING	VESA
COMMUNICATION INTERFACE	USB-A (1)
WORKING VOLTAGE	5V + 5%/-10 THROUGH USB PORT
CURRENT CONSUMPTION	MAX 100mA
OPERATING ENVIRONMENT	-40°C TO +70°C
OPERATING HUMIDITY	5% TO 90%
STORAGE ENVIRONMENT	-55°C TO +85°C
PRODUCT WEIGHT	2.0 LBS (0.907 KG)

TESTING

DROP: MIL-STD-810H 516.8
VIBRATION: MIL-STD-810H 514.8
CRASH: SAE J1455 30MPH
CYCLE: DOCK AND UNDOCK FOR 20K CYCLES
ENVIRONMENTAL:
 HOT/COLD OPERATING -20°C TO 50°C (-4°F TO 122°F)
 HOT/COLD STORAGE -40°C TO 85°C (-40°F TO 185°F)

- Public sector, warehouse, cold storage, transportation/logistics
- Low profile with ergonomic design & feel
- Keyboard features **86 keys with integrated pointing device**
- USB-A cable provided for wired connection (coiled & straight)
- Tested to withstand 5 Million Actuations per Key
- IP65 rated design
- Dual molded materials ensures strength, ruggedness and extreme temperature resistance
- Water resistant splash guard (Mil Std 810 compliant from top side)
- Rugged testing including crash, vibration, thermal, drop, and dock/undocking
- Integrated VESA mounting pattern

- Backlit dimming ideal for nighttime or ambient-light use
- LED backlighting good for life of product (200,000 hr LED's)
- Constructed from chemically resistant resin for lasting durability and easy cleaning

PART DETAILS

HAVIS PART ID	COLOR	TOUCHPAD LOCATION	BACKLIGHT COLOR	# OF KEYS	NUMBER PAD	USB	BLUETOOTH	IP RATING	KEY MATERIAL
KB-1006	BLACK	CENTER	RED	86	×	✓	×	IP65	PLASTIC