

# HAVIS DOCKING STATION FOR PANASONIC TOUGHBOOK 33 TABLET

DS-PAN-1200 SERIES



## RUGGED MOBILITY FOR MAXIMUM EFFICIENCY

- Panasonic certified electronics with advanced port replication includes both HDMI and VGA video capability as well as standard options to support mission-critical peripherals
- Full access to computer features & ports
- 2 front mounted USB 2.0 ports
- Standard & Advanced I/O options
- Dual pass-thru antenna connections (optional)
- Spring-loaded connector head
- Powered by LIND 120W vehicle adapter (LPS-103, sold separately)
- Compatible with hand strap and high capacity batteries
- Intelligent cable management system
- Integrated VESA 75 mounting pattern
- Lock and key for theft deterrence



## HAVIS DOCKING STATION FOR PANASONIC TOUGHBOOK 33 TABLET

DS-PAN-1200 SERIES

### PANASONIC TOUGHBOOK 33 SOLUTION

- Low profile, lightweight and flexible design
- Port replication with integrated strain relieving
- Dual Pass-Thru Antenna Connections (Optional)
- External Power Supply (Optional)
- Bundles available for convenient solutions



PART NUMBER	ETHERNET	USB 2.0	USB 3.0	HDMI	VGA	SERIAL	POWER INPUT	PASS THRU ANT	ANT TYPE	EXT POWER
DS-PAN-1201	2	2 REAR 2 FRONT	2 REAR			1	15.6 V*			
DS-PAN-1201-2	2	2 REAR 2 FRONT	2 REAR			1	15.6 V*	DUAL	TNC	
DS-PAN-1202	2	2 REAR 2 FRONT	2 REAR			1	15.6 V*			LPS-103
DS-PAN-1202-2	2	2 REAR 2 FRONT	2 REAR			1	15.6 V*	DUAL	TNC	LPS-103
DS-PAN-1203										
DS-PAN-1204	2	2 REAR 2 FRONT	2 REAR	1	1	1	15.6 V*			
DS-PAN-1204-2	2	2 REAR 2 FRONT	2 REAR	1	1	1	15.6 V*	DUAL	TNC	
DS-PAN-1205	2	2 REAR 2 FRONT	2 REAR	1	1	1	15.6 V*			LPS-103
DS-PAN-1205-2	2	2 REAR 2 FRONT	2 REAR	1	1	1	15.6 V*	DUAL	TNC	LPS-103
DS-PAN-1206										LPS-103

\*Requires an external Panasonic authorized DC power supply

### SPECIFICATIONS:

Height: 11.8 in (30.0 cm)  
 Width: 12.9 in (32.7 cm)  
 Depth: 3.5 in (8.9 cm)  
 Weight: 3.1 lbs (1.4 kg)  
 Mounting: VESA 75 & RAM 2.25"  
 Ball

### CERTIFICATIONS & TESTING:

TOUGHBOOK, CE, C-Tick, E- Mark Certified; RoHS  
 Compliant, UL Listed  
 Vibration Testing: MIL-STD-810H 514.8  
 Impact Test: Crash Simulation per SAE J1455  
 Cycle Test: Latch Tested 30,000 cycles  
 Environmental Testing: Hot/Cold Operation & Storage

