DOCKING SOLUTIONS FOR PANASONIC TOUGHBOOK 33/33 5G & 34 TABLETS

DS-PAN-1210 SERIES







VERSATILE SOLUTIONS FOR RUGGED APPLICATIONS

- Supports Panasonic's TOUGHBOOK 33 and TOUGHBOOK 33 5G Tablets
- Optional port replication with Advanced or Standard content
- Optional Dual pass-through antenna connection
- Spring-loaded, floating connector head
- One-handed docking & undocking
- Havis Power Supply (optional)
  - *Refer to SKU chart for compatibility
- Compact & lightweight while being ultra rugged
- Lock and key supplied for peace of mind theft deterrence

DOCKING SOLUTIONS FOR PANASONIC TOUGHBOOK 33/33 5G & 34 TABLETS

DS-PAN-1210 SERIES



PANASONIC TOUGHBOOK 33 & TOUGHBOOK 34

- Intelligent cable management system
- Integrated VESA 75 mounting pattern
- Polycarbonate construction ensures strength, ruggedness and extreme temperature resistance
- Rounded edges and corners for comfort and safety
- Made in USA

PART NUMBER	ETHERNET	USB 2.0	USB 3.0	HDMI	VGA	SERIAL	PASS-THRU ANT	ANT TYPE	EXT POWER
DS-PAN-1211	2	4	2			1			
DS-PAN-1211-2	2	4	2			1	2	TNC	
DS-PAN-1212N	2	4	2			1			INCL.
DS-PAN-1212N-2	2	4	2			1	2	TNC	INCL.
DS-PAN-1213									
DS-PAN-1214	2	4	2	1	1	1			
DS-PAN-1214-2	2	4	2	1	1	1	2	TNC	
DS-PAN-1215N	2	4	2	1	1	1			INCL.
DS-PAN-1215N-2	2	4	2	1	1	1	2	TNC	INCL.

SPECIFICATIONS:

Height: 11.8" (300mm)
Width: 12.9” (327 mm)
Depth: 3.5” (89 mm)
Weight: 3.3 lbs (1.49 kg)

CERTIFICATIONS & TESTING:

Vibration Testing: MIL-STD 810H 514.8
Crash Testing: SAE J1455 30mph
Cycle Testing: Dock/undock 30K cycles
Environmental Testing: Hot/Cold operational -10° C to 50° C (14° F to 122° F); Hot/Cold storage -40° C to 85° C (-40° F to 185° F)
Thermal Shock: MIL-STD 810H, Method 503.7
FCC, CE, CAN ICES (B), RoHS
EMC Testing: EN 55032, EN 50498
ESD: IEC 10605