

RUGGED USB BACKLIT KEYBOARD WITH CENTER TOUCHPAD



SPECIFICATIONS

DIMENSIONS	12"L x 7.75"W x 1.25"D (340.85 x 196.85 x 31.75 mm)
MOUNTING	VESA 75 AND AMPS
COMMUNICATION INTERFACE	USB-A (1)
WORKING VOLTAGE	5V + 5%/-10 THROUGH USB PORT
CURRENT CONSUMPTION	MAX 100mA
OPERATING ENVIRONMENT	-20°C TO +70°C
OPERATING HUMIDITY	99%
STORAGE ENVIRONMENT	-20°C TO +70°C
PRODUCT WEIGHT	2.0 LBS (0.907 KG)

TESTING

DROP: MIL-STD-810H 516.8
VIBRATION: MIL-STD-810H 514.8
CRASH: SAE J1455 30MPH
CYCLE: DOCK AND UNDOCK FOR 20K CYCLES
ENVIRONMENTAL:
 HOT/COLD OPERATING -20°C TO 50°C (-4°F TO 122°F)
 HOT/COLD STORAGE -40°C TO 85°C (-40°F TO 185°F)

- Public sector, warehouse, transportation/logistics
- Low profile with ergonomic design & feel
- Keyboard features **83 rubber keys with splash proof touchpad** and two sealed mouse buttons
- USB-A cable provided for wired connection (coiled & straight)
- Rubber key, full travel switches
- Sealed to prevent water intrusion (Mil Std 810 compliant)
- Backlit dimming ideal for nighttime or ambient-light use
- Red backlighting good for life of product (200,000 hr LED's)
- Tested to withstand 10 Million Actuations per Key
- IP65 rated design
- Integrated VESA 75 and AMPS mounting pattern
- Rugged testing including crash, vibration, thermal, drop, and dock/undocking
- Dual molded materials ensures strength, ruggedness and extreme temperature resistance
- Constructed from chemically resistant resin for lasting durability and easy cleaning

PART DETAILS

HAVIS PART ID	COLOR	TOUCHPAD LOCATION	BACKLIGHT COLOR	# OF KEYS	NUMBER PAD	USB	BLUETOOTH	IP RATING	KEY MATERIAL
KB-1011	BLACK	CENTER	RGB	83	✗	✓	✗	IP65	PLASTIC