

DOCKING STATIONS FOR DELL PRO RUGGED 14 LAPTOPS (PR514260)

DS-DELL-1300 SERIES



BUILT FOR PERFORMANCE

The DS-DELL-1300 Series keeps operators moving with one-handed docking and a spring-loaded, floating connector head that holds a steady connection over rough routes. Optional port replication and Quad pass-through antenna support give you the connectivity each deployment demands.

- Optional port replication with Advanced or Standard content
- Updated one-handed docking & undocking with pull latch
- Includes 120W Havis Power Supply (120N-A01-T01-1) in select models
- Optional quad pass-through antenna connection
- Compatible with DS-DA-426 Screen Support, designed to support the laptop screen and reduce vibration
- Spring-loaded, floating connector head





DELL PRO RUGGED 14 LAPTOPS (PR514260)

Built ultra rugged yet compact, the DS-DELL-1300 Series is tested to MIL-STD 810H and rated for 30,000 dock and undock cycles to hold up through years of daily field use. VESA 75 mounting and a supplied lock and key round out a secure, integrated in-vehicle setup.

- Compact & lightweight while being ultra rugged
- Lock and key supplied for peace of mind theft deterrence



PR514260

PART DETAILS

PART NUMBER	ETHERNET (RJ45)	USB-C 3.2	USB 3.2	HDMI	POWERED SERIAL (DB9)	PASS-THRU ANT (QUAD)	POWER SUPPLY
DS-DELL-1301	1	1 FRONT	3 REAR	1	1		
DS-DELL-1301-4	1	1 FRONT	3 REAR	1	1	SMA	
DS-DELL-1302N	1	1 FRONT	3 REAR	1	1		120N-A01-T01-1
DS-DELL-1302N-4	1	1 FRONT	3 REAR	1	1	SMA	120N-A01-T01-1
DS-DELL-1303							
DS-DELL-1305	1	1 FRONT	3 REAR		1		
DS-DELL-1305-4	1	1 FRONT	3 REAR		1	SMA	
DS-DELL-1306N	1	1 FRONT	3 REAR		1		120N-A01-T01-1
DS-DELL-1306N-4	1	1 FRONT	3 REAR		1	SMA	120N-A01-T01-1

SPECIFICATIONS

HEIGHT:	2.54 IN (6.45 CM)
WIDTH:	12.54 IN (31.85 CM)
DEPTH:	10 IN (25.4 CM)
WEIGHT:	2.27 LBS (1.02 KG)
MOUNTING:	VESA 75

CERTIFICATIONS & TESTING

VIBRATION TESTING	MIL-STD 810H 514.8
CRASH TESTING	SAE J1455 30MPH
BUMP TESTING	IEC-68-2006-27
CYCLE TESTING	DOCK/UNDOCK 30K CYCLES
ENVIRONMENTAL TESTING	HOT/COLD OPERATIONAL -31° C TO 63° C (-23.8° F TO 145° F); HOT/COLD STORAGE -40° C TO 85° C (-40° F TO 185° F)
THERMAL SHOCK	MIL-STD 810H, METHOD 503.7
EMC TESTING	EN 55032, EN 50498
ESD	IEC 10605