

## 14" CAPACITIVE TOUCH SCREEN DISPLAY WITH INTEGRATED HUB



## NEXT GENERATION TOUCH SCREEN DISPLAYS

Designed for demanding environments, our Next Generation Touch Screen Displays deliver larger 14" displays, 1200 nits of brightness, and fully integrated hubs, keeping your team connected, wherever the job takes them.

- On-board integrated HUB for DeX compatibility
- Integrated microphone for voice calls
- 1200 nits of brightness
- Front facing button placement (power, input selector, volume, brightness)
- Power button allows screen to be blacked out for privacy without full reboot
- Night mode offers red monochrome for reduced eye strain
- All I/O ports with integrated strain relieving
- 14" touch screen display with 10 pt capacitive touch gorilla glass
- Integrated camera for video calls
- Pair of 4W front-facing stereo speakers
- Indicator lights communicate when TSD is powered up and when a device is connected
- Sleep mode equipped to reduce power consumption
- On-board I/O includes gigabit Ethernet, HDMI 2.0, superspeed USB-C and multiple USB 3.1 type A ports





## HAVIS TOUCH SCREEN DISPLAYS

Meet the next generation of rugged touch screen displays.

Bigger, brighter, and built to keep your team productive wherever the job takes them.

### PART DETAILS

FEATURE	TSD-201 (PREVIOUS GENERATION)	TSD-301	TSD-302
14" DISPLAY (1920 X 1200, 16:10)		X	X
12.5" DISPLAY (1920 X 1080, 16:9)	X		
INTEGRATED CAMERA			X
INTEGRATED MICROPHONE		X	X
FRONT FACING 4W STEREO SPEAKERS	X	X	X
FRONT FACING BUTTON PLACEMENT		X	X
1200 NITS BRIGHTNESS	X	X	X
10-POINT CAPACITIVE GORILLA GLASS	X	X	X
INTEGRATED DEX HUB	X	X	X
HDMI 2.0			X
HDMI 1.4	X		
GIGABIT ETHERNET	X	X	X
USB-C UPSTREAM WITH POWER DELIVERY	X	X	X
HIGHER POWER PD (UP TO 60W / 20V @ 3A)		X	X
DOWNSTREAM USB-C PORT			X
MULTIPLE USB-A 3.1 PORTS	X		X
INPUT SELECTOR SWITCH (USB-C / HDMI)	X		X
NIGHT MODE (RED MONOCHROME SETTING)	X	X	X
SLEEP MODE	X	X	X
PRIVACY BLACKOUT BUTTON	X	X	X
VESA 75 MOUNTING PATTERN	X	X	X
MIL-STD 810H VIBRATION TESTING	X	X	X
SAE J1455 30 MPH CRASH TESTING	X	X	X
THERMAL SHOCK & HUMIDITY TESTING (MIL-STD-810H)	X	X	X

### SPECIFICATIONS

HEIGHT: 10.56" (26.8 CM)

WIDTH: 13.62" (34.6 CM)

DEPTH: 1.40" (3.6 CM)

WEIGHT: 8.5 LBS / 3.85 KG

MOUNTING: VESA 75

### CERTIFICATIONS & TESTING

#### VIBRATION TESTING

MIL-STD 810H 514.8

#### CRASH TESTING

SAE J1455 30MPH CRASH TESTING

#### BUMP TESTING

IEC-60068-2-27

#### ENVIRONMENTAL TESTING

HOT/COLD OPERATIONAL & STORAGE,  
THERMAL SHOCK (MIL-STD-810H-503.7),  
HUMIDITY (MIL-STD-810H-507.6)

#### REGULATORY

FCC, ICES-003, CE, UKCA, ROHS, REACH